



THE ULTIMATE FLOORING EXPERIENCE

Tarkett Holding GmbH • Rheinallee 13 • 67061 Ludwigshafen • info.de@tarkett.com • 0621 / 68172 300

Tarkett products	tooth	recommended ARDEX adhesives				
		France	Benelux	D-A-CH	Russia Eastern Europe	others
LINOLEUM xf ²	TKB B1	ARDEX AF 180 or ARDEX AF 181W or ARDEX AF 270 or ARDEX AF 785				
LINOLEUM xf ² SD	TKB S2	ARDEX AF 2270				
LINOLEUM xf ² SILENCIO	TKB B1	ARDEX AF 155 or ARDEX AF 785 or ARDEX AF 2224				
Elafono (Cork Underlay)	TKB B1	ARDEX AF 270 or ARDEX AF 785 or ARDEX AF 2224				
HETEROGENEOUS PVC - Compact	TKB A1 TKB A2	ARDEX AF 155 or ARDEX AF 2224				

Preparation of the substrate

The substrate must meet the requirements of DIN 18365 "Floor covering work". In particular, it must be level, permanently dry, solid, load-bearing, free of release agents and cracks, and resistant to tensile and compressive forces, or it must be prepared accordingly. Leveling work is carried out with suitable ARDEX leveling compounds in conjunction with ARDEX primers.

In the ARDEX system

Floor covering work is carried out with suitable ARDEX adhesives. In combination with other ARDEX products classified in EMICODE EC1, optimum conditions for very low-emission and low-odor construction. Observe the technical data sheets of the products. We guarantee the perfect quality of our products. Our processing recommendations are based on tests and practical experience; however, they can only be general information without guarantee of properties, as we have no influence on the construction site conditions and the execution of the work. Country-specific regulations based on regional standards, building codes, processing or industry guidelines may result in specific processing recommendations.



THE ULTIMATE FLOORING EXPERIENCE

Tarkett Holding GmbH • Rheinallee 13 • 67061 Ludwigshafen • info.de@tarkett.com • 0621 / 68172 300

Tarkett products	tooth	recommended ARDEX adhesives				
		France	Benelux	D-A-CH	Russia Eastern Europe	others
HETEROGENEOUS PVC - Acoustic	TKB A1 TKB A2	ARDEX AF 155 or ARDEX AF 2224				
HOMOGENEOUS NON-PVC : iQ One	TKB A2	ARDEX AF 140 or ARDEX AF 155				
HOMOGENEOUS PVC	TKB A1 TKB A2	ARDEX AF 155 or ARDEX AF 2224				
CONDUCTIVE HO FLOORINGS – tiles (over copper strip for sheets)	P 7	ARDEX AF 2270				
HETEROGENEOUS PVC - LVT	TKB A1 TKB A2	ARDEX AF 140 or ARDEX AF 155 or ARDEX AF 180				

Preparation of the substrate The substrate must meet the requirements of DIN 18365 "Floor covering work". In particular, it must be level, permanently dry, solid, load-bearing, free of release agents and cracks, and resistant to tensile and compressive forces, or it must be prepared accordingly. Leveling work is carried out with suitable ARDEX leveling compounds in conjunction with ARDEX primers.

In the ARDEX system Floor covering work is carried out with suitable ARDEX adhesives. In combination with other ARDEX products classified in EMICODE EC1, optimum conditions for very low-emission and low-odor construction. Observe the technical data sheets of the products. We guarantee the perfect quality of our products. Our processing recommendations are based on tests and practical experience; however, they can only be general information without guarantee of properties, as we have no influence on the construction site conditions and the execution of the work. Country-specific regulations based on regional standards, building codes, processing or industry guidelines may result in specific processing recommendations.



THE ULTIMATE FLOORING EXPERIENCE

Tarkett Holding GmbH • Rheinallee 13 • 67061 Ludwigshafen • info.de@tarkett.com • 0621 / 68172 300

Tarkett products	tooth	recommended ARDEX adhesives				
		France	Benelux	D-A-CH	Russia Eastern Europe	others
HETEROGENEOUS PVC – LVT Specific conditions (high traffic...)	TKB A2	ARDEX AF 180 or ARDEX AF 181W or ARDEX AF 495				
HETEROGENEOUS NON PVC - LVT	TKB A2	ARDEX AF 140 or ARDEX AF 155				
HETEROGENEOUS NON PVC – LVT Specific conditions (high traffic...)	TKB A2	ARDEX AF 180 or ARDEX AF 181W or ARDEX AF 495				
HETEROGENEOUS NON PVC – LVT Specific conditions (tackifier)	Roller, TKB A1	ARDEX AF 825				
Protectwall	TKB A1 TKB A2	ARDEX AF 155 or ARDEX AF 181W				

Preparation of the substrate The substrate must meet the requirements of DIN 18365 "Floor covering work". In particular, it must be level, permanently dry, solid, load-bearing, free of release agents and cracks, and resistant to tensile and compressive forces, or it must be prepared accordingly. Leveling work is carried out with suitable ARDEX leveling compounds in conjunction with ARDEX primers.

In the ARDEX system Floor covering work is carried out with suitable ARDEX adhesives. In combination with other ARDEX products classified in EMICODE EC1, optimum conditions for very low-emission and low-odor construction. Observe the technical data sheets of the products. We guarantee the perfect quality of our products. Our processing recommendations are based on tests and practical experience; however, they can only be general information without guarantee of properties, as we have no influence on the construction site conditions and the execution of the work. Country-specific regulations based on regional standards, building codes, processing or industry guidelines may result in specific processing recommendations.



THE ULTIMATE FLOORING EXPERIENCE

Tarkett Holding GmbH • Rheinallee 13 • 67061 Ludwigshafen • info.de@tarkett.com • 0621 / 68172 300

Tarkett products	tooth	recommended ARDEX adhesives				
		France	Benelux	D-A-CH	Russia Eastern Europe	others
Aquarelle	TKB A2	ARDEX AF 155 or ARDEX AF 181W				
Lino Wall	TKB B1	ARDEX AF 181W or ARDEX AF 270 or ARDEX AF 785				
Tarkolay (for HE and HO)	TKB A1 TKB A2	ARDEX AF 155 or ARDEX AF 180				
Contact adhesive – skirtings, stairs	Roller	ARDEX AF 635				
Tackifler	Roller	ARDEX AF 825				

Preparation of the substrate The substrate must meet the requirements of DIN 18365 "Floor covering work". In particular, it must be level, permanently dry, solid, load-bearing, free of release agents and cracks, and resistant to tensile and compressive forces, or it must be prepared accordingly. Leveling work is carried out with suitable ARDEX leveling compounds in conjunction with ARDEX primers.

In the ARDEX system Floor covering work is carried out with suitable ARDEX adhesives. In combination with other ARDEX products classified in EMICODE EC1, optimum conditions for very low-emission and low-odor construction. Observe the technical data sheets of the products. We guarantee the perfect quality of our products. Our processing recommendations are based on tests and practical experience; however, they can only be general information without guarantee of properties, as we have no influence on the construction site conditions and the execution of the work. Country-specific regulations based on regional standards, building codes, processing or industry guidelines may result in specific processing recommendations.



THE ULTIMATE FLOORING EXPERIENCE

Tarkett Holding GmbH • Rheinallee 13 • 67061 Ludwigshafen • info.de@tarkett.com • 0621 / 68172 300

Substrate preparation					
Filler	ARDEX K 22F / K 39 / K 40		ARDEX K 22F / K 60 / FA 20	ARDEX K 39 / K 40 / K 22F	ARDEX K 39 / K 40 / K 55
Primer	ARDEX P 52		ARDEX P 82	ARDEX P 21	
Filling/spackling	ARDEX A 45 / A 45 FEIN Crack repair : ARDEX FB / PU 5 / P 10 SR		ARDEX FIX	-	
Substrate, new, permanently dry	Calcium sulfate according to DIN 18560 - CA/CAF	Screed/Concrete according to DIN EN 13813 and DIN 18560 - CT	Wood substrates	Mastic asphalt according to DIN 18560 - AS	Old substrate tile

Preparation of the substrate The substrate must meet the requirements of DIN 18365 "Floor covering work". In particular, it must be level, permanently dry, solid, load-bearing, free of release agents and cracks, and resistant to tensile and compressive forces, or it must be prepared accordingly. Leveling work is carried out with suitable ARDEX leveling compounds in conjunction with ARDEX primers.

In the ARDEX system Floor covering work is carried out with suitable ARDEX adhesives. In combination with other ARDEX products classified in EMICODE EC1, optimum conditions for very low-emission and low-odor construction. Observe the technical data sheets of the products. We guarantee the perfect quality of our products. Our processing recommendations are based on tests and practical experience; however, they can only be general information without guarantee of properties, as we have no influence on the construction site conditions and the execution of the work. Country-specific regulations based on regional standards, building codes, processing or industry guidelines may lead to specific processing recommendations